

XP CARTS

PORTABLE LIGHTING - EXPLOSION PROOF

Industrial • Task Lighting

Lighting for Explosive Environments - The LE551 Portable Light Cart is manufactured in accordance with applicable NFPA standards. For use in hazardous environments and laboratory applications. Portable lighting solutions for hazardous atmospheres. Light can be directed where you need it most. Fixture(s) sold separately.

LDPI recommends consulting local authorities for approval of your application prior to purchase.





	LE551		V1				РВ
1	2	3	4	5	6	7	8

1 CART	2 SERIES	3 SOURCE	4 VOLTAGE	5 CCT	6 OPTIC	7 SHROUD	8 FINISH
4372-2: 2 Row Cart 4372-3: 3 Row Cart 4372-4: 4 Row Cart	LE551	L3: 43W (4 Ft. 2 Row) L4: 64W (4 Ft. 2 Row) L5: 73W (4 Ft. 3 Row) L6: 86W (4 Ft. 3 Row) L7: 87W (4 Ft. 4 Row) L8: 128W (4 Ft. 4 Row)	V1 : 120-277VAC (50/60 Hz)	4 : 4,000K 5 : 5,000K	BLANK: None D: Diffused Acrylic	E: Enclosed	Standard product will be Black with red accent.

FIXTURE LISTINGS

UL listed 844 U.S. and Canada for hazardous locations UL listed 1598 U.S. and Canada for wet locations UL listed 1598A U.S. and Canada for marine locations

FEATURES

For either 2, 3 or 4 row, 4ft fixtures 5" non-sparking casters (1 pair fixed, 1 pair swivel) 360° non-continuous adjustable fixture rotation Polycarbonate shield option

ELECTRICAL

Available in 43W, 64W, 73W, 86W, 87W or 128W Voltages: 120V 50 Ft. of S.O. electric cable suitable for rough duty use Explosion proof switch Explosion proof plug - 120 Volts (P/N 3825)

HOUSING

Frame constructed of corrosion resistant aluminum

REFLECTOR

One piece aluminum reflector

LENS


Clear tempered glass tubes, polycarbonate shield.

MOUNTING

Fixture mounted to 360° (non-continuous) adjustable rotating brackets

OPTIONS

2 row model (P/N 4372-2) 3 row model (P/N 4372-3) 4 row model (P/N 4372-4)



XP CARTS


PORTABLE LIGHTING - EXPLOSION PROOF

Industrial • Task Lighting

DIMENSIONS


2/3/4 LED LAMP CARTS

- A 58.0"
- B 24.0"
- C 24.75"
- D 57.63"









2 Row LED 4 Row LED

